



13 July 2022

To Whom It May Concern

EASY FLOOR APPLICATION

Mixx Cement thin film coatings has been used successfully in various light commercial applications including guesthouses, restaurants, hair dressing salons etc.

Easy floor is a thin film cement coating with a finished film thickness of 1.6 – 1.8 mm. Easy floor is available in 8 (eight) Colours and is suitable for household and light commercial surfaces like boutique type stores, guesthouses, restaurants etc. It is imperative to understand that the substrate to which any cement coating is applied must be of a specific standard and strength. A minimum of 25 Mpa and no more than 5% moisture content as well as adequate expansion joints and all building done in accordance to NHBRC regulations is necessary to avoid unnecessary pre preparation or disappointment of the end result.

Cement coatings applied to a substrate that is going to be heavily used should be applied by a contractor with the experience necessary to understand substrates fully. It is important to understand that Mixx Cement cannot guarantee a third party application and it is in the best interest for the consumer to do the necessary due diligence and ensure that the contractor specified has the necessary knowledge and know how of the product and that you are comfortable in the experience and ability of the contractor to deliver the finished product you desire. It is also important to note that Easy floor is a cement coating and will wear accordingly, it does however wear beautifully and gains its own character over time.

A data sheet as well as material safety sheets are attached for your perusal.

Kindest regards

Moya Blight

Managing Director